



L90H - C S - DC12V

Relay Type:-

Contact Form:- 1C

Type of Sealing:- S: Sealed Type

Coil Voltage:- 5~110VDC

Model		L90H			
Features	Dimension L * W * H (mm)	32.2 * 27.6 * 20.1			
	Terminal Type	PCB			
	Weight	28gm approximately			
Contact Data	Contact Form	1C			
	Contact Material	Ag Alloy			
	Contact Capacity	NO:- 40A @250VAC / 30VDC		NC:- 30A @250VAC / 30VDC	
	Contact Resistance	100mΩ Max. (at 1A / 6VDC)			
Coil Data	Coil Voltage	5 ~ 110VDC			
	Coil Power Consumption	0.9W			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage Max. (VDC)	Drop Out Voltage Min. (VDC)
		12VDC	155	75 %	10 %
24VDC	660	75 %	10 %		
General Data	Dielectric Strength	1500VAC (Between open Contacts)			
		1500VAC (Between coil & Contacts)			
	Insulation Resistance	100MΩ 500VDC			
	Operate Time	15ms			
Release Time	10ms				
Dimension					
Application	Television, Stereo, Microwave, Air Conditioner, Refrigerator, Iron, Electrical Boiler, Satellite Receiver, etc.				