



Contact Rating

Contact Form	2C	3C
Contact Resistance	50mΩ (1A 6VDC)	50mΩ (1A 6VDC)
Contact Capacity	10A 250VAC/28VDC	10A/5A(NO/NC) 250VAC/28VDC

General Specification

Insulation Resistance	500MΩ, 500VDC
Dielectric Strength	1000VAC (Between Open Contact) 1500VAC (Between Coil & Contact)
Operating Time	30ms/20ms

Coil Rating

Nominal Coil Power	1.5W, 2.5VA
Coil Voltage	6,12,24,48,100,110VDC, 6,12,24,48,110/120,220,240VAC

Coil Data Chart

Nominal Voltage VDC	Pull in Voltage VDC	Release Voltage VDC	Coil Resistance Ω ±10%	Nominal Voltage VAC	Pull in Voltage VAC	Release Voltage VAC	Coil Resistance Ω ±10%
6	4.80	0.60	24	6	4.80	1.80	14.5
12	9.60	1.20	96	12	9.60	3.60	20
24	19.20	2.40	384	24	19.20	7.20	80
48	38.40	4.80	1540	48	38.40	14.40	320
100	80.0	10.0	9600	110/120	88.0	36.00	1700
110	88.0	11.0	9650	220/240	176.00	72.00	7400/8760

Dimension Bottom View

